

**120F0283****Reciprocating compressor, NTZ136A3LR1B**

Refrigerants: R404A; R452A, Segment usage: Refrigeration LT, Compressor power supply [V]: 200-230/3/60, Packing format: Single pack

PRODUCT DETAILS

Gross weight	37.5 Kg
Net weight	35 Kg
Volume	61.54 Liter
EAN	5702428665292
Approval	CE UL UKCA
Brand technique	Reciprocating compressor
Capacity control	Fixed speed
China RoHS compliance	Out of scope
Colour	Blue
Compressor power supply [V]	200-230/3/60
Configuration code	Single
Connection type	Rotolock
Cylinder	2
Description	NTZ136-3B
Diameter [mm]	288 mm
Discharge connection height [mm]	74 mm
Discharge connection pipe size [in]	3/4 in
Discharge connection size [in]	1 1/4 in
Drawing number	8502012g
Economizer	No
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(a), 6(a)-I, 7(a), 7(c)-I, 8(b), 9(b)
Factory HP [bar]	25 bar
Factory LP [bar]	25 bar
Family	NTZ
Fitting remark	(shipped with rotolock version only)
Fitting sleeve	ODF
Fitting standard	Rotolock
Frequency [Hz]	60
Gauge port HP	None
Gauge port LP	Schrader
Glass mounting	Threaded
Glass torque [Nm]	50 N-m
GP LP torque [Nm]	15 N-m
High Side TS Max	150 °C
High Side TS Min	-35 °C

Product Detail | Reciprocating compressor, NTZ136A3LR1B

PRODUCT DETAILS

High Side Volume	0.6 L
High value of nominal voltage at 60Hz [V]	230 V
High value of voltage range at 60Hz [V]	253 V
In scope of WEEE and contain batteries	No
IP protection class	IP55 (with cable gland)
Low Side TS Max	50 °C
Low Side TS Min	-35 °C
Low Side Volume	16.5 L
Low value of nominal voltage at 60Hz [V]	200 V
Low value of voltage range at 60Hz [V]	180 V
LRA	97.2 A
Max pressure (PS) - high side	28.5 bar
Max pressure (PS) - low side	22.6 bar
MCC	29 A
Model number	NTZ136A3LR1B
Motor protection	Internal overload protector
Mounting torque [Nm]	15 N-m
Network power supply [V/Ph/Hz]	208-230/3/60
Number of starts per hour [Max]	12
Oil charge [L]	1.8 L
Oil equalization	3/8" flare SAE
Oil equalization torque [Nm]	30 N-m
Oil reference	175PZ
Packaging height [mm]	450 mm
Packaging length [mm]	385 mm
Packaging width [mm]	375 mm
Packing format	Single pack
Packing quantity	1
Phase	3
Power connections	Spade
Product group	Hermetic compressors
Product Name Description	NTZ
Refrigerant charge [kg] [Max]	5 kg
Refrigerants	R404A R452A
Rotational speed at 60Hz [rpm]	3500 rpm
Segment usage	Refrigeration LT
Shipped fittings	Suction and discharge solder sleeves, rotolock nuts, and gaskets
Shipped instructions	Installation instructions
Shipped mounting	Mounting kit with grommets, bolts, nuts, sleeves and washers
Shipped oil	Initial oil charge
Suction connection height [mm]	265 mm
Suction connection material	-
Suction connection pipe size [in]	1 1/8 in
Suction connection size [in]	1 3/4 in

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Reciprocating compressor, NTZ136A3LR1B
PRODUCT DETAILS

Swept volume [cm³]	136 cm ³
Technology	Reciprocating
Test Dif [bar] [Max]	30 bar
Test HP [bar] [Max]	30 bar
Test LP [bar] [Max]	25 bar
Torque earth [Nm]	3 N-m
Torque power [Nm]	3 N-m
Total height [mm]	413 mm
Type	NTZ136
UK RoHS compliance	Out of scope
Viscosity [cP]	32 cP

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Accessories

120Z0764 [🔗](#)
Mounting, Compressor kit

Mounting kit 2 cylinder HP


8156132 [🔗](#)
Connector, GASKET

Gasket, 1-3/4"


8153004 [🔗](#)
Connector, Solder Sleeve

Solder sleeve, P02 (1-3/4" rotolock, 1-1/8" ODF)


8153008 [🔗](#)
Connector, Solder Sleeve

Solder sleeve, P04 (1-1/4" rotolock, 3/4" ODF)


8156134 [🔗](#)
Electrical component, Terminal box

Service kit for terminal box 80 x 96 mm, including 1 cover, 1 clamp


120Z0576 [🔗](#)
Acoustic hood, Reciprocating

Acoustic hood for two-cylinder compressor

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



8156131 [🔗](#)
Connector, GASKET
 Gasket, 1-1/4"



8156009 [🔗](#)
Connector, GASKET
 Gasket set, 1", 1-1/4", 1-3/4", OSG gaskets black and white



7750009 [🔗](#)
Electrical component, Discharge thermostat kit
 Discharge thermostat kit

Spare Parts



8156145 [🔗](#)
Connector, GASKET
 Gasket for oil sight glass (black chloroprene)



8168029 [🔗](#)
Connector, Rotolock service valve
 Rotolock valve, V04 (1-1/4" rotolock, 3/4" ODF)



7703009 [🔗](#)
Connector, Valve set
 Valve set, V02 (1-3/4"~1-1/8"), V04 (1-1/4"~3/4")



7773107 [🔗](#)
Crankcase heater, Belt heater
 Belt type crankcase heater, 65 W, 230 V, CE mark, UL



7773109 [🔗](#)
Crankcase heater, Belt heater
 Belt type crankcase heater, 65 W, 110 V, CE mark, UL



120Z0459 [🔗](#)
Crankcase heater, PTC heater
 PTC heater 27W, CE mark, UL

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Spare Parts

**8156019** [🔗](#)**Connector, Sight glass**Oil sight glass with gaskets (black and white)

**8168028** [🔗](#)**Connector, Rotolock service valve**Rotolock valve, V02 (1-3/4" rotolock, 1-1/8" ODF)

**120Z0638** [🔗](#)**Lubricant, 175PZ**POE lubricant, 175PZ, 1-litre can

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.